


# MSI-3360 Challenger 2 Specifications and Dimensions

The MSI-3360 crane scale is an ideal unit for the cost conscious user for light capacity use. For higher capacities, heavy-duty, outdoor and continuous production use, MSI recommends MSI-4260, MSI-4300, MSI-6260CS or MSI-9300.



CAPACITY	RESOLUTION**	A	B	C	D	E	F	APPROX. SHIP WT.
250 lb	0.1 lb	11.94 in	2.45	2.00	1.12	1.63	1.12	22 lb
125 kg	.05 kg	303 mm	62.0	51.0	28.0	41.0	28.0	10 kg
500 lb	0.2 lb	11.94 in	2.45	2.00	1.12	1.63	1.12	22 lb
250 kg	0.1 kg	303 mm	62.0	51.0	28.0	41.0	28.0	10 kg
1,000 lb	0.5 lb	11.94 in	2.45	2.00	1.12	1.63	1.12	22 lb
500 kg	0.2 kg	303 mm	62.0	51.0	28.0	41.0	28.0	10 kg
2,000 lb	1 lb	11.94 in	2.45	2.00	1.12	1.63	1.12	22 lb
1,000 kg	0.5 kg	303 mm	62.0	51.0	28.0	41.0	28.0	10 kg
5,000 lb	2 lb	16.67 in	3.40	2.45	1.80	2.50	1.81	39 lb
2,500 kg	1 kg	423 mm	86.0	62	46.0	64.0	46.0	18 kg
10,000 lb	5 lb	16.67 in	3.40	2.45	1.80	2.50	1.81	39 lb
5,000 kg	2 kg	423 mm	86.0	62	46.0	64.0	46.0	18 kg
15,000 lb	5 lb	21.58 in	4.28	3.25	1.95	3.00	2.25	67 lb
7,000 kg	2 kg	548 mm	109	83	50	76	57	30 kg

CONSULT FACTORY FOR HIGHER CAPACITIES

## Standard Product Specifications

**Accuracy:** Plus or minus 0.1% of applied load  
**Display:** 5 digit, 1.2 in/30mm high manual or photocell LED brightness control

**Filtering:** Low, Medium or High selectable

**Units:** Pounds or Kilograms selectable

**Resolution:** 2000 or 2500 divisions standard (up to 10,000 available)

**Power:** 6 volt rechargeable battery (115 or 230 VAC charger included)

**Operating Time:** 50 - 100 hours depending on operating mode

**Auto-Off Mode:** Select for 12 minutes, 1 hour or Off

**Auto-Sleep Mode:** Power down during non-use and power up with motion for maximum battery conservation

**Service Counter:** Registers number of lifts by value for inspection and maintenance reminder

**Operating Temperature Range:** -4° to +122°F (-20° to +50°C)

**Enclosure:** NEMA 12/IP54 powder coated Alodined Cast Aluminum

**Hook:** Crosby-Laughlin or equivalent 360° non-bearing swivel

**Safe Overload:** 200% of rated capacity

**Ultimate Overload:** 500% of rated capacity

## Function Switches and Lights

**POWER:** Turns unit ON or OFF

**ZERO:** Zeros applied load up to 100% of capacity (limited range with NIST or OIML option)

**TARE:** Tares out applied load and displays weight in Net mode. Push again to return to Gross mode

**USER:** User programmable multifunction switch for use as TEST, UNIT select, TOTAL (auto or manual), PEAK HOLD and SET POINTS

**ANNUNCIATORS:** Center of Zero, Net, Gross, Total, Peak, x 1000, Battery, lb/kg, Motion, SP1 and SP2

## Options and Accessories

- NTEP (86-021A2), OIML and EC (T2943) approved versions (Contact factory for specifications)
- Infrared remote controller with 8 meter operating range
- RS-232 data output with connector
- Universal direct power supply
- Audible setpoint alarm
- Special capacity or displayable resolution

## Other Heavy-Duty MSI Crane Scales



For heavy-duty, high heat or hazardous use applications, See MSI-4260 Port-A-Weigh specification sheet.

Capacities from 500 lb to 500,000 lb (250kg to 250,000kg).



For heavy-duty and multi-task applications, See MSI-4300 Porta-Weigh Plus specification sheet.

Capacities from 500 lb to 500,000 lb (250kg to 250,000kg).



For heavy-duty applications requiring remote radio telemetry display and/or remote computer/printer interface, see MSI-9300 Porta-Weigh Plus specification sheet.

Capacities from 500 lb to 500,000 lb (250kg to 250,000kg).

*"We weigh quality first"*

## MSI Measurement Systems International

14240 Interurban Avenue South STE.200  
 Seattle, Washington 98168-4661 U.S.A.  
 Phone: 206-433-0199 • Fax: 206-244-8470  
 Web: www.msiscalcs.com • Email: info@msiscalcs.com



Specifications subject to change without notice.

PUB.127-05-90J  
 © 2004 by Measurement Systems International, Inc.  
 Printed in U.S.A.